



VLFT.EX15142
Special System Water Control Valves, Deluge Type

[Page Bottom](#)

Special System Water Control Valves, Deluge Type

[See General Information for Special System Water Control Valves, Deluge Type](#)

FIREGUARD SAFETY EQUIPMENT CO LTD

EX15142

2ND FL
145-157 ST JOHN ST
LONDON, ECV1 4PY UNITED KINGDOM

Model A, 2, 3, 4, 6 and 8 in. sizes, deluge valves for vertical installation only with a rated pressure of 175 psig. For operation by dry pilot line, manually, electrically or wet pilot line of sprinklers. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model DSK-AD skid mounted for operation by dry pilot line of sprinklers, manually or electrically and Model DSK-AW mounted on skid for operation by wet pilot line of sprinklers, manually or electrically in 2, 3, 4, 6 and 8 in. sizes for vertical installation only with working pressure not to exceed 175 psig. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model DPACK-AD skid mounted with pack for operation by dry pilot line sprinklers, manually, electrically and Model DPACK-AW for operation with wet pilot line sprinklers, manually, electrically in 2, 3, 4, 6 and 8 in. sizes for vertical installation only with working pressure not to exceed 175 psig. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model H, 3, 4 and 6 in. sizes, deluge valves for horizontal or vertical installations only with a rated pressure of 175 psig. For operation by dry pilot line, manually, electrically or wet pilot line of spinklers. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model C1, 2, 3, 4, 6 and 8 in. sizes, deluge valves for horizontal or vertical installations only with a rated pressure of 250 psig. For operation by dry pilot line, manually, electrically or wet pilot line of spinklers. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model D1, 2, 3, 4, 6 and 8 in. sizes, deluge valves for horizontal or vertical installations only with a rated pressure of 250 psig. For operation by dry pilot line, manually, electrically or wet pilot line of spinklers. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

Model N1, 2, 3, 4, 6 and 8 in. sizes, deluge valves for horizontal or vertical installations only with a rated pressure of 250 psig. For operation by dry pilot line, manually, electrically or wet pilot line of spinklers. Height of pilot line above valve limited as shown in the Installation Instructions. For accessories used with these valves, see listing under "Accessories for Special Systems".

[Last Updated](#) on 2012-11-28

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.