



Fire Fighting Hose

Technical Data

FIRE FIGHTING HOSE

MODEL: FGH105A

According to BS 6391-1983

GENERAL DESCRIPTION

Fireguard produces various types fire fighting hoses with high quality for most demanding situations. All hoses are manufactured according to BS 6391-1983 TYPE 3.

The Fireguard Advance rubber covered fire hose is the no. 1 choice for firefighters worldwide. This hose features: tough durable and abrasion resistant, resistance to oil, fuel and a wide range of chemicals, resistance to heat, UV and ozone, has excellent adhesion between rubber and textile, no cleaning and drying is required and easy to repair.

Applications: Applications include: refineries, chemical industry, military, fire brigades, marine and offshore installations, fire hose for usage under tough conditions.

Construction –Synthetic Woven Textile Reinforcement: EPDM lining with synthetic woven textile reinforcement and nitrile rubber cover. Totally embedded in the rubber compound providing excellent protection against mechanical damage



FIRE GUARD

MODEL: FGH105A

Standard Lengths: 15, 20, 30m (50, 66 100ft), in bore size 38/65mm (1 ½" & 2 ½"), other lengths on request.

Standard Colour: Red.

Valid Standards: prEN 1924 / BS 6391 / Type 3 and other national standards

Features

- Oil & Chemical Resistance
- Heat Resistance
- Abrasion Resistance
- Maintenance Free
- Easy to Repair
- Weather Resistance

Technical Data:

Working pressure: 17bar

Bursting pressure: 50bar

Weight:

1 ½": 0.35Kg/M

2 ½" : 0.57Kg/M