



# Globe Hydrant Valves

## BS 5041 PT 1

Horizontal

Right Angle

Oblique

Bib Nose



- Dual Seat Type
- For Marine & On-shore Applications
- Inlet: Flanged or Threaded
- Outlet: 2½" Inst. Female
- Other International Outlets Available: Storz, NOR, JIS, N&S, NH etc



Full Range of International Hydrant Valves Available

# Globe Hydrant Valves


## GENERAL DESCRIPTION

Fire hydrant valves are suitable for both offshore and onshore application. They are manufactured to BS 5154 and BS 5041 part 1.


The valves are manufactured in corrosion resistant materials with an LG2 gunmetal body and are available with both British Instantaneous female outlet to BS 336 and a wide range of International outlets.

## FEATURES


All Fireguard Fire hydrant valves are dual seat type. The primary valve seat is hard rubber with an additional secondary metal to metal seat.




Horizontal



Oblique



Bib Nose



Right Angle

## TECHNICAL DATA

Flanged Inlet	PN16 1½"	PN16 2"	PN16 2½"	TABLE D/E 2½"	TABLE D/E 3"	ANSI 2½"	ANSI 3"
Diameter (mm)	150	165	185	165	184	178	191
PCD (mm)	110	125	145	127	146	140	152

Also available with alternative flanged and BSP, NPT threaded inlets.

## WEIGHTS

Valve Type (Instantaneous)	Right Angle	Horizontal	Oblique	Bib Nose
Weight: Flanged Inlet	9Kg	9Kg	9Kg	9Kg
Threaded Inlet	8Kg	8Kg	8Kg	8Kg

In line with our policy of continuous improvement we reserve the right to amend any specification without notice.