



Industrial Speakers

Features:

AP15-TUC:

- 15W High Efficiency Compression Driver
- 25 or 70VRMS field selectable
- Vandal-Resistant, Weatherproof Construction
- Recommended for High Intelligibility Paging, Intercommunication, and Signaling

Amplified Speakers:

- 24VDC polarized operation (120VAC on some models)
- Die cast aluminum circuitry housing
- Indoor or outdoor mounting.
- NEMA 3 rated enclosure

Description:


The Industrial Series includes:
15W Fire Rated Loudspeaker
Amplified Speakers, Hazardous Area Amplified Speakers and Explosion Proof Speakers.

equipped with a compression driver providing up to 15 watts RMS power handling capability, and weather resistant metal construction.


The ASHP, ASHH, ASHX series speakers provide additional power to a system without having to add more amplifiers.

All are designed for surface mounting.


Ordering Information:



AP15-TUC



Amplified Speaker



Amplified Speaker



Explosion Proof Amplified Speaker

Listings:



S5661



6911-1446:100

Model Number

Description

AP-15TUC

Fire Rated Horn speaker., grey - *std color*, red - *opt*.
25/70V 1/2, 1, 2, 4, 7-1/2, 15W taps.

ASHP-24SMR-25

24VDC, 25VRMS Speaker Amplifier

ASHP-24SMR-70

24VDC, 70VRMS Speaker Amplifier

ASHP-ACSMR-25

120VAC, 25VRMS Speaker Amplifier

ASHP-ACSMR-70

120VAC, 70VRMS Speaker Amplifier

ASHH-24SMR-25

Division 2 Hazardous Area

Speaker Amplifier 24VDC, 25VRMS

ASHH-24SMR-70

Speaker Amplifier 24VDC, 70VRMS

ASHX-24SMR-25

Explosion Proof (Class I, Div. 1, Groups B, C, & D)

Speaker Amplifier 24VDC, 25VRMS

ASHX-24SMR-70

Speaker Amplifier 24VDC, 70VRMS



Specifications:

Model Number	Power Rating	Frequency Response	Sound Output	
			UL 3dB increment	Anechoic
AP-15TUC	15 Watts continuous	400 - 4,000 Hz	102db@10' 15W	120db@1meter 15W (peak)

Model Number	Input Voltage	Standby Current	Wattage Draw @ 25Vrms)	UL dB(A) Sound Pressure	dB(A) Sound Power
ASHP Series	24VDC	.060A	.015W	97	118.7
ASHH Series	24VDC	.060A	.015W	97	118.7
ASHX Series	24VDC	.060A	.015W	97	118.7

Specifications are subject to change without notice. Specifications are provided for information only and no responsibility is assumed by Fireguard Safety Equipment Co Ltd. For their use.